



## GRADE D ROTARY AND VIBRATOR HOSE KASS CATPRESS

DESIGNED FOR MUD DELIVERY, MOTION COMPENSATING OR DECOKING APPLICATION

**TUBE:** RUBBE.

**COVER:** NITRILE.

**REINFORCEMENT:** MULTIPLE STEEL WIRE SPIRALS.

**TEMPERATURE RANGE:** -40°C + 93°C

**APPLICATIONS:** USED IN OIL FIELD WELL CEMENTING, WELL PULLING , PETROLEUM GEOLOGY EXPLORATION, SMALL DRILLING MACHINE, WATER CONVEYANCE, COAL EXCAVATION. USED TO CARRY SLURRY, NORMAL TEMPERATURE WATER, AND OTHER FLUIDS.

**SECTORS:** OILFIELD, CONSTRUCTION, MINING

TECHNICAL SPECIFICATIONS OF D RANK ROTARY / DRILLING HOSE

Part Number	Rotary hose I.D		Rotary hose O.D	Working Pressure		Test Pressure		Min Bend Radius	Weight
	Inch	mm		MPa	PSI	MPa	PSI		
KMRTH-32	2"	51	69	35	5000	70	10000	900	5.7
KMRTH-40	2-1/2"	64	84	35	5000	70	10000	1100	6.7
KMRTH-48	3	76	107	35	5000	70	10000	1200	16.2
KMRTH-56	3-1/2"	89	120	35	5000	70	10000	1300	18.4
KMRTH-64	4"	102	133	35	5000	70	10000	1400	20.3

**EXTRA:**

- SUPPLIED WITH HYDROSTATIC TEST
- QUALITY TEST SUPPLIED