



2201 CONCRETE HOSE 1300 PSI

HIGH PRESSURE HOSE DESIGNED TO HANDLE THE PUMPING OF CONCRETE, PLASTER OR GROUT MIXTURE.

TUBE: SBR AND NR.

COVER: SBR AND NR.

REINFORCEMENT: STEEL CORD BRAID.

TEMPERATURE RANGE: -10°C AND +75°C.

APPLICATIONS: HEAVY DUTY PUMPING APPLICATIONS FOR CONSTRUCTION SECTORS

SECTORS: CONSTRUCTION, HEAVY INDUSTRIES.

TECHNICAL SPECIFICATIONS CONCRETE HOSE

Part Number	ID		OD	WP	BP	min BR	Steel braids	Weight
	Inch	mm	mm	PSI	PSI	mm		Kg/m
2201-32	2"	51±0.7	69	1300	3000	200	2	2.80
2201-40	2-1/2"	64±0.8	84	1300	3000	250	2	4.30
2201-48	3	76±1.0	107	1300	3000	270	4	6.00
2201-64	4"	130±1.75	120	1300	3000	300	4	9.10
2201-80	5"	127±1.0	133	1300	3000	360	4	17.00

EXTRA:

- PIPE FITTINGS, CLAMPS AND NOZZLES ARE SUPPLIED.